

B22

FEMALE HEADER WITH SQUARE TAIL PROFILE : 11.0mm STRAIGHT

PITCH: 2.54mm

SPECIFICATIONS

Material

Insulator : PBT, glass reinforced, rated UL 94V-0

Contact : Brass

Electrical

Current Rating : 1 Amp


Contact Resistance : 30 mΩ max.

Insulation Resistance : 3000 MΩ min.







Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40°C to +105°C


♦ Mating Suggestion : C15, C16, C17 & C18 series.



B



RECOMMENDED P.C.B LAYOUT



RECOMMENDED P.C.B LAYOUT

HOW TO ORDER:

B22 - - - - -

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.PIN LENGTH	5.INSULATOR COLOR
SINGLE ROW 1*2 - 1 *40 DUAL ROW 2*2 - 2*40	A: BRASS	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	A: 3.2mm B: 6.0mm C: 7.9mm D: 12.0mm	1. BLACK